

# 19"/2<sup>®</sup> 16-p Switch ESW443



The 19"/2<sup>®</sup> 16-port Switch ESW443 is a powerful managed switch which features sixteen 1 Gbps access ports. An ideal solution for demanding high speed networks, including data, video, and voice services. It supports both layer 2 and layer 3 functionality and can be implemented anywhere high speed LAN and WAN connectivity may be required.

## Built to take a beating

The switch is built from the ground up to withstand the harshest conditions over the long haul. It has an Aluminium casing and it runs on ruggedized hardware which makes it suitable for harsh environments. It is a sealed unit that requires no active cooling and provides interfaces over military-grade circular connectors. The unit features a military-grade power supply supporting ground/marine (MIL-STD-1275D) vehicle voltage input. On top of this toughness, we offer lifetime support to ensure that the switch maintains its performance for many years to come.

## Mounting

All 19"/2 units can be mounted together in several different ways:

- One 19"/2 unit can be mounted in a 19" rack
- Two 19"/2 units can be mounted together in a 19" rack
- Two or more devices can also be stacked on top of each other

# 19"/2® 16-p Switch ESW443

| Technical Specification    |  |
|----------------------------|--|
| Description                | Ethernet switch with 16x 1Gbit copper  |
| Bridging                   | 802.1q VLAN, 802.1d STP  |
| Routing support            | Yes (static routing)   |
| Backbone Speed             | 48 Gbps  |
| Interface (front)          | 10 x LAN RJ45 (10/100/1000 Mbps)<br>1 x DC in, 10-32V (ITS)                        |
| Interface (back)           | 6 x LAN RJ45(10/100/1000 Mbps)<br>1 x Console Serial<br>1 x Service port (Binder)  |
| Power Consumption          | ≤ 35W  |
| Transient power protection | Designed to meet MIL-STD-1275D   |
| Case                       | Aluminium  |
| Dimensions                 | 220 x 280 x 44 mm (W x D x H w/o connectors)<br>220 x 290 x 44 mm ( /w connectors) |
| Weight                     | ≤ 3kg  |
| Certification              | Designed to meet IP65, MIL-STD-810G, MIL-STD-461F and MIL-STD-1275D                |
| Other                      | No fans  |

Designed to meet:

| MIL-STD-810F   | Operating   | Storage                                   |
|--|---|---|
| Altitude<br>Method 500.5,<br>( <i>procedure II,III</i> )                     | 4572 m (15000 ft)                                 | Rapid decompression<br>12192 m (40000 ft) |
| Humidity<br>Method 507.5   | Aggravated, 95% RH duration 5 days                | -   |
| Shock<br>Method 516.5,<br>( <i>procedure I, IV</i> )                         | 40 G, 11 ms (Terminal-peak saw tooth shock pulse) | 122 cm (26 drops)*                        |
| Salt fog<br>Method 509.5,<br>( <i>Procedure I</i> )                          | -   | Threshold: 4x 24-hrs                      |
| Temperature<br>Method 501.5 &<br>Method 502.5,<br>( <i>procedure I, II</i> ) | -40 °C to 55 °C<br>(-40 °F to 131 °F)             | -40 °C to 70 °C<br>(-40 °F to 158 °F)     |
| Temperature shock<br>Method 503.5<br>( <i>procedure I</i> )                  | -40 °C to +55 °C<br>(-40 °F to +131 °F)           | -   |
| Vibration<br>Method 514.6  |   |   |
| - <i>Category 2</i>  | -   | √   |
| - <i>Category 14</i>   | √   | -   |
| - <i>Category 20 a &amp; b</i>   | √   | -   |

\* Only with optional Peli Case

Designed to meet:

| MIL-STD-461F                  | Limitation                   | Threshold                                  |
|-------------------------------|------------------------------|--|
| EMI radiated<br>Method RE102  | 2 MHz to 18 GHz              | Ground Applications,<br>Navy Mobile & Army |
| EMI radiated<br>Method RS103  | 2 MHz to 1 GHz               | Army                                       |
| EMI conducted<br>Method CE102 | 10 kHz to 10 Mhz             | Basic Curve                                |
| EMI conducted<br>Method CS101 | 30 Hz to 150 kHz             | Curve #1                                   |
| EMI conducted<br>Method CS114 | 10 kHz to 200 MHz            | Army, Ground                               |
| EMI conducted<br>Method CS115 | Tested according to standard | Army                                       |
| EMI conducted<br>Method CS116 | 10 kHz to 100 MHz            | Army                                       |

