



Model Comparison MC700 Series

	MC701	MC702	MC703	MC704	MC705	MC706	MC708	MC709	MC710	MC711	MC712
Interface A	1000Base-LX Single Mode 1310nm (PRO BEAM® mini)	1000Base-LX Single Mode 1310nm (LC)	100Base-FX Multi Mode 1300nm (LC)	100Base-SX Multi Mode 850nm (PRO BEAM® mini)	1000Base-SX Multi Mode 850nm (LC)	1000Base-SX Multi Mode 850nm (HMC)	100 or 1000 Mbps* Multi Mode 850nm (HMC)	E1 interface (RJ45)	1000Base-SX Multi Mode 850nm (HMC)	100BASE-FX Multi Mode 1300 nm (LC)	1000Base-LX Single Mode 1310nm (PRO BEAM® mini)
Interface B	1000Base-T (RJ45)	1000Base-T (RJ45)	1000Base-T (RJ45)	1000Base-T (RJ45)	1000Base-T (RJ45)	1000Base-T (RJ45)	100 or 1000 Mbps* Single Mode 1310nm (HMC)	1000Base-T (RJ45)	1000Base-T (RJ45)	1000BASE-LX Single Mode 1310nm (LC)	100Base-SX Multi Mode 850nm (PRO BEAM® mini)
Power in	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)	10-32V DC (ITS)
Power in (USB)	5V DC (Binder)	5V DC (Binder)	5V DC (Binder)	5V DC (Binder)	5V DC (Binder)	5V DC (Binder)	-	5V DC (Binder)	5V DC (Binder)	5V DC (Binder)	-

* Speed must be the same on both interfaces