

# 19"/6 MC718



## Rugged ethernet media converter

The MC718 converts between 1000BASE-T (Copper Gigabit Ethernet) and 1000BASE-LX (Fiber Gigabit Singlemode Ethernet)

### Small form factor

The MilDef 19"/2" form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

### Flexible mounting

The 19"/2" standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

### Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

### Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

### Features

- 10-32 VDC
- Passively cooled

### Connector Interfaces

5V DC (front)	• 1x USB 2.0
X1 DC IN (front)	• 1x Power
X2 (front)	• 1x ETH 1000BASE-T
X3 (back)	• 1x 1000BASE-LX

### Other Interfaces

1x Status indicator (front)

### Technical Specification

LAN 1000BASE-LX	1000BASE-LX standard with SM 1310 nm fiber
LAN 1000BASE-T	1000BASE-T standard
Electronics ground to chassis	Isolated
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Polarity protection	Protected against polarization failure on the power input in the voltage range of normal operation
Power consumption	5 W
Power input	10-32 VDC
Power to chassis	Isolated
Power to electronics ground	Isolated
Chassis material	Aluminum
Coating and color	Dupont AE0305-1101320 (RAL 1013)
Cooling	Passively cooled
Dimensions	73 x 43.4 mm (2.9 x 1.7 in) (WxH)
Dimensions depth	172 mm (6.8 in)
Earth point	M6 12 mm
Surface treatment chassis	Chromit-Al
Weight	0.7 kg (1.6 lbs)
MTBF	671,169 h
CE	Compliant

### Environmental Specification

Functional shock - Operating	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40 g 11 ms
High temperature - Operating	MIL-STD-810G, Method 501.5, Procedure II - Operation 55 °C (131 °F)

### High temperature - Storage

MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)

### Humidity

MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 % RH Ten 24 h cycles

### IP Class (Solid Particle Protection) IP Class 6X

### IP Class (Water)

IP Class X5

### Low air pressure - Rapid decompression

MIL-STD-810G, Method 500.5, Procedure III - Rapid decompression 75.2 kPa, corresponding to 2,438 m (8,000 ft) 17 kPa, corresponding to 12,192 m (40,000 ft)

### Low air pressure - Operating

MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4,572 m (15,000 ft)

### Low temperature - Operating

MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)

### Low temperature - Storage

MIL-STD-810G, method 502.5, Procedure I - Storage -40 °C (-40 °F)

### Noise level

Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance

### Salt fog

MIL-STD-810G Method: 509.5 5 % ± 1 % (by weight) Two cycles, 24 h wet + 24 h dry / cycle

### Temperature shock - Operating

MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) -40 °C (-40 °F)

### Vibration - Helicopter

MIL-STD-810G, Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter

### Vibration - Loose cargo

MIL-STD-810G, Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo

### Vibration - Tracked vehicles

MIL-STD-810G, Method: 514.6, Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles

### Vibration - Wheeled vehicles

MIL-STD-810G, Method: 514.6, Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles

**EMC Specification**

<b>EMI conducted CE102</b>	MIL-STD-461F, Method CE102, Conducted emissions, power leads BASIC CURVE 10 kHz - 10 MHz
<b>EMI radiated RE102</b>	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 2 MHz - 18 GHz
<b>EMS conducted CS101</b>	MIL-STD-461F, Method CS101, Conducted susceptibility, power leads CURVE #1 30 Hz - 150 kHz
<b>EMS conducted CS114</b>	MIL-STD-461F, Method CS114, Conducted bulk susceptibility Army, Ground 10 kHz - 200 MHz
<b>EMS conducted CS115</b>	MIL-STD-461F, Method CS115, Conducted susceptibility, bulk cable injection, impulse excitation
<b>EMS conducted CS116</b>	MIL-STD-461F, Method CS116, Conducted susceptibility, damped sinusoidal transients, cables and power leads 10 kHz - 100 MHz
<b>EMS radiated RS103</b>	MIL-STD-461F, Method RS103, Radiated susceptibility, electric field Army 2 MHz - 1 GHz