

19"/6 Mediaconverter MC706



Media converter

The MC706 is a rugged media converter for converting 50/125 850nm multimode to RJ45, or vice versa.

Built to take a beating

The media converter is made to withstand the harshest conditions over the long haul. It features aluminium casing, rugged MIL connectors for easy integration and will operate down to -40 C.

Guaranteed performance

Our products always come with a lifetime support to ensure your equipment maintains peak performance for many missions to come. We also serve units and stock spare parts for 5 years end-of-life.

Features

- Passively cooled

19"/6 Mediaconverter MC706

Connector Interfaces	
1Gbit 850nm MM (front)	• 1x ETH 1000BASE-SX
LAN (front)	• 1x ETH 1000BASE-T
5V DC (front)	• 1x USB 2.0
DC IN (back)	• 1x Power

Other Interfaces	
1x Status indicator (front)	

Technical Specification	
Blanking	Enable/disable all externally visible indicators from emitting light via the "blinking command"
LAN 1000BASE-SX	1000BASE-SX standard with MM 850nm fiber
LAN	1000BASE-T standard
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Power consumption	5W
Coating and color	Dupont AE0305-6603120 (RAL6031)
Cooling	Passively cooled
Dimensions	73x44x147 mm (2,9x1,8x5,8 inch) (WxHxD)
Earth point	M6 12mm
Surface treatment chassis	Chromit-Al
Weight	1 kg (2,2 lbs)
MTBF	Greater than 25000 h

Environmental Specification (* designed to meet)	
Functional Shock - Operating*	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40g 11 ms
High temperature - Operating*	MIL-STD-810G, Method 501.5, Procedure II - Operation 55° C (131° F)
High temperature - Storage*	MIL-STD-810G, Method 501.5, Procedure I - Storage 71° C (160° F)
Humidity*	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 %rh Ten 24-hour cycles
IP Class (Water)*	IP Class X4
IP Class (solid foreign object)*	IP Class 5X

Low air pressure - Rapid Decompression*	MIL-STD-810G, Method 500.5, Procedure III - Rapid Decompression 75.2kPa, corresponding to 2,438m (8,000 ft) 17kPa, corresponding to 12192m (40,000 ft)
---	--

Low air pressure - Operating*	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4572m (15,000 ft)
-------------------------------	---

Low temperature - Operating*	MIL-STD-810G, method 502.5, Procedure II - Operation -40° C (-40° F)
------------------------------	--

Low temperature - Storage*	MIL-STD-810G, method 502.5, Procedure I - Storage -40° C (-40° F)
----------------------------	---

Noise level*	Maximum noise level of 40dB SPL A-weighting @ 1m (3,3 ft) distance
--------------	--

Salt fog*	MIL-STD-810G Method: 509.5 5% +/- 1% (by weight) Two cycles, 24h wet + 24h dry /cycle
-----------	---

Temperature Shock - Operating*	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55° C (131° F) - 40° C (-40° F)
--------------------------------	---

Transit drop, in shipping package*	MIL-STD-810G, method 516.6, Procedure IV - Transit Drop. Table 516.6-VI, Transit drop test, < 45.4 kg (100 lbs), < 91 cm (36 inch), Manpacked or man-portable
------------------------------------	---

Vibration - Helicopter*	MIL-STD-810G, Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
-------------------------	--

Vibration - Loose Cargo*	MIL-STD-810G, Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
--------------------------	---

Vibration - Tracked Vehicles*	MIL-STD-810G, Method: 514.6, Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles
-------------------------------	---

Vibration - Wheeled Vehicle*	MIL-STD-810G, Method: 514.6, Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles
------------------------------	---

EMC Specification (* designed to meet)	
CE EMI*	EN61000-6-3:2007
CE EMS*	EN55032:2015
EMI conducted CE102*	MIL-STD-461F, Method CE102 BASIC CURVE 10kHz to 10MHz

19"/6 Mediaconverter MC706

EMI radiated RE102*	MIL-STD-461F 2MHz - 18Ghz Navy Mobile & Army
EMS conducted CS101*	MIL-STD-461F, Method CS101, conducted susceptibility, power leads CURVE #1 30Hz to 150kHz
EMS conducted CS114*	MIL-STD-461F 10kHz - 200MHz Army, Ground
EMS conducted CS115*	MIL-STD-461F Conducted susceptibility, bulk cable injection, impulse excitation
EMS conducted CS116*	MIL-STD-461F 10 kHz to 100 MHz
EMS radiated RS103*	MIL-STD-461F 2MHz to 1GHz Army
ESD*	EN61000-4-2:2009 Level 3 EN50024:1998 Performance criteria B + A1:2001 + A2:2003