

# 19"/2 Server CS1121



## Xeon Server in a 19inch2 form factor

The CS1100 series provides a power full Xeon server optimized for virtual server applications. It comes with a 3 disk hardware RAID and a wide range of interfaces and options. It is optimized for low size, weight and power (SWaP) to meet industry requirements without sacrificing reliability, ruggedness or performance.

### Mounting

The 19"/2 standard enables flexible mounting with customized brackets. The unit can be mounted in a 19" rack, half racks, directly to a surface and in any angle.

### Built to take a beating

The Computer is built to withstand the harshest conditions over the long haul. It features aluminum casing, rugged MIL connectors and IP65 rated disk caddies to enable the unit to work in demanding environments.

## Guaranteed performance

Our products always come with a lifetime support to ensure your equipment maintains peak performance for many missions to come. We also serve units and stock spare parts for 5 years after end-of-life.

## Features

- Up to 128 GB RAM
- Intel Xeon D1577 processor
- 16 cores (32 threads)
- RAID 0, 1, 5
- IPMI 2.0
- Optimized for VMWare
- Replaceable CMOS battery

# 19"/2 Server CS1121

## Connector Interfaces

COM1 (front)	• 1x COM
DC IN (front)	• 1x Power
ETH0 - ETH3 (front)	4 connectors which each has: <ul style="list-style-type: none"> <li>• 1x ETH 1000BASE-T</li> </ul>
ETH IPMI (back)	• 1x ETH 100BASE-T
FAN (back)	• 1x FAN 12V
SERVICE (back)	• 1x RS232 Service
SD (back)	• 1x SD card reader
USB1/2 (front)	• 2x USB 2.0
USB3/4 (front)	• 2x USB 3.0
USB5/6 (back)	• 2x USB 3.0
VGA (front)	• 1x VGA

## Other Interfaces

3x MilDef Disk Slot (front)
1x Mute Button (front)
1x System Button (front)

## Technical Specification

Computer Memory	Up to 128 GB RAM
Computer Processor	Intel Xeon D1577 processor
Computer Storage	RAID 0, 1, 5
IPMI access	IPMI 2.0
MUTE functionality	When pressing the MUTE button be able to enable/disable all fans and externally visible indicators from emitting light.
Optimized for VMWare	Optimized for VMWare
CMOS Battery	Replaceable CMOS battery, located behind a cover for easy access.
<b>WMI Support</b>	
Polarity protection	Protected against polarization failure on the power input in the voltage range of normal operation.
Power consumption	150W
Power input	16-32 VDC
Coating and color	Dupont AE0305-6603120 (RAL6031)
Dimensions Width and Height	220x88mm (WxH)
Earth point	M6 12mm
Rack Mounting depth	400mm
Surface treatment chassis	Chromit-Al
Weight	8 kg

## Environmental Specification (\* designed to meet)

Functional shock, operating*	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment
High temperature - Operating*	MIL-STD-810G, method 501.5, Procedure II - Operation 55 °C
High temperature - Storage*	MIL-STD-810G, method 501.5, Procedure I - Storage 71 °C
Humidity*	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 %rh
IP Class (Solid Particle Protection)*	IP Class 6X
IP Class (Water)*	IP Class X5
Low air pressure - Rapid Decompression*	MIL-STD-810G, Method 500.5, Procedure III - Rapid Decompression
Low air pressure - operating*	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4572m (15.000 ft)
Low temperature - Operational*	MIL-STD-810G, method 502.5, Procedure II - Operation -40 C
Low temperature - Storage*	MIL-STD-810G, method 502.5, Procedure I - Storage -40 C
Noise level*	Maximum noise level of 40dB SPL A-weighting @ 1m distance
Salt fog*	MIL-STD-810G Method: 509.5
Temperature Shock - Operating*	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 C - 40 C
Transit drop, in shipping package*	MIL-STD-810G, method 516.6, Procedure IV - Transit Drop. Table 516.6-VI, Transit drop test, < 45.4 kg, < 91 cm, Manpacked or man-portable
Vibration - Helicopter*	MIL-STD-810G, Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
Vibration - Loose Cargo*	MIL-STD-810G, Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
Vibration - Tracked vehicles*	MIL-STD-810G, Method: 514.6 , Procedure 1 - General Vibration,

# 19"/2 Server CS1121

Category 20 - Ground vehicles -  
ground mobile, tracked vehicles

**Vibration - Wheeled Vehicle\*** MIL-STD-810G, Method: 514.6 ,  
Procedure 1 - General Vibration,  
Category 20 - Ground vehicles -  
ground mobile, wheeled vehicles

## EMC Specification (\*designed to meet)

<b>CE EMI*</b>	EN61000-6-3:2007
<b>CE EMS*</b>	EN55022:2010
<b>EMI conducted CE102*</b>	MIL-STD-461F, Method CE102 BASIC CURVE 10kHz to 10MHz
<b>EMI radiated RE102*</b>	MIL-STD-461F 2MHz - 18Ghz Navy Mobile & Army
<b>EMS conducted CS101*</b>	MIL-STD-461F, Method CS101, conducted suceptibility, power leads CURVE #1 30Hz to 150kHz
<b>EMS conducted CS114*</b>	MIL-STD-461F 10kHz - 200MHz Army, Ground
<b>EMS conducted CS115*</b>	MIL-STD-461F
<b>EMS conducted CS116*</b>	MIL-STD-461F 10 kHz to 100 MHz
<b>EMS radiated RS103*</b>	MIL-STD-461F 2MHz to 1GHz Army
<b>ESD*</b>	EN61000-4-2:2009 Level 3 EN50024:1998 Performance criteria B + A1:2001 + A2:2003