

19"/2 Server CS1122



Xeon Server in a 19inch2 form factor

The CS1100 series provides a power full Xeon server optimized for virtual server applications. It comes with a 3 disk hardware RAID and a wide range of interfaces and options. It is optimized for low size, weight and power (SWaP) to meet industry requirements without sacrificing reliability, ruggedness or performance.

Mounting

The 19"/2 standard enables flexible mounting with customized brackets. The unit can be mounted in a 19" rack, half racks, directly to a surface and in any angle.

Built to take a beating

The Computer is built to withstand the harshest conditions over the long haul. It features aluminum casing, rugged MIL connectors and IP65 rated disk caddies to enable the unit to work in demanding environments.

Guaranteed performance

Our products always come with a lifetime support to ensure your equipment maintains peak performance for many missions to come. We also serve units and stock spare parts for 5 years after end-of-life.

Features

- Up to 128 GB RAM
- Intel Xeon D1548 CPU
- Up to 8 cores (16 threads)
- RAID 0, 1, 5
- Minimum 1024x768 resolution
- IPMI 2.0
- Replaceable CMOS battery
- Compatible with VMware ESXi 6.5

19"/2 Server CS1122

Connector Interfaces

COM1 (front)	• 1x COM
DC IN (front)	• 1x Power
ETH0-ETH2 1G (front)	3 connectors which each has: <ul style="list-style-type: none"> • 1x ETH 1000BASE-T
ETH3 10G (front)	• 1x ETH 10GBASE-T
ETH IPMI (back)	• 1x ETH 100BASE-T
FAN (back)	• 1x FAN
SERVICE (back)	• 1x RS232 Service
SD (back)	• 1x SD card reader
USB3/4 (front)	• 2x USB 2.0
USB5/6 (back)	• 2x USB 3.0
USB1/2 (front)	• 2x USB 3.0
VGA (front)	• 1x VGA

Other Interfaces

3x MilDef Disk Slot (front)
1x System Button (front)

Technical Specification

Blanking	Double-pressing the System button
Computer Memory	Up to 128 GB RAM
Computer Processor	Intel Xeon D1548 CPU
Computer Storage	RAID 0, 1, 5
Display resolution minimum	Minimum 1024x768 resolution
IPMI access	IPMI 2.0
CMOS Battery	Replaceable CMOS battery, located behind a cover for easy access.
VMware ESXi 6.5	Compatible with VMware ESXi 6.5
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Polarity protection	Protected against polarization failure on the power input in the voltage range of normal operation.
Power consumption	160W
Power input	16-32 VDC
Coating and color	Dupont AE0305-6603120 (RAL6031)
Dimensions Width and Height	220x88mm (8,7x3,5 inch) (WxH)
Earth point	M6 12mm
Rack Mounting depth	400mm (17,4 inch)
Surface treatment chassis	Chromit-Al
Weight	8 kg (17,7 lbs)
MTBF	Greater than 25000 h

Environmental Specification (* designed to meet)

Functional Shock - Operating*	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40g 11 ms
High temperature - Operating*	MIL-STD-810G, Method 501.5, Procedure II - Operation 55C (131F)
High temperature - Operating*	MIL-STD-810G, method 501.5, Procedure II - Operation 60 °C (140 °F)
High temperature - Storage*	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)
Humidity*	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 %rh Ten 24-hour cycles
IP Class (Solid Particle Protection)*	IP Class 6X
IP Class (Water)*	IP Class X5
Low air pressure - Rapid Decompression*	MIL-STD-810G, Method 500.5, Procedure III - Rapid Decompression 75.2kPa, corresponding to 2,438m (8.000 ft) 17kPa, corresponding to 12192m (40.000 ft)
Low air pressure - Operating*	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4572m (15.000 ft)
Low temperature - Operating*	MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)
Low temperature - Storage*	MIL-STD-810G, method 502.5, Procedure I - Storage -40 C (-40 °F)
Noise level*	Maximum noise level of 40dB SPL A-weighting @ 1m (3,3 ft) distance
Salt fog*	MIL-STD-810G Method: 509.5 5% +- 1% (by weight) Two cycles, 24h wet + 24h dry /cycle
Temperature Shock - Operating*	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) - 40 °C (-40 °F)
Transit drop, in shipping package*	MIL-STD-810G, method 516.6, Procedure IV - Transit Drop. Table 516.6-VI, Transit drop test, < 45.4

19"/2 Server CS1122

kg (100 lbs), < 91 cm (36 inch),
Manpacked or man-portable

Vibration - Helicopter*	MIL-STD-810G. Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
Vibration - Loose Cargo*	MIL-STD-810G. Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
Vibration - Tracked Vehicles*	MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles
Vibration - Wheeled Vehicle*	MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles

EMC Specification (* designed to meet)

CE EMI*	EN61000-6-3:2007
CE EMS*	EN55032:2015
EMI conducted CE102*	MIL-STD-461F, Method CE102 BASIC CURVE 10kHz to 10MHz
EMI radiated RE102*	MIL-STD-461F 2MHz - 18Ghz Navy Mobile & Army
EMS conducted CS101*	MIL-STD-461F, Method CS101, conducted susceptibility, power leads CURVE #1 30Hz to 150kHz
EMS conducted CS114*	MIL-STD-461F 10kHz - 200MHz Army, Ground
EMS conducted CS115*	MIL-STD-461F Conducted susceptibility, bulk cable injection, impulse excitation
EMS conducted CS116*	MIL-STD-461F 10 kHz to 100 MHz
EMS radiated RS103*	MIL-STD-461F 2MHz to 1GHz Army
ESD*	EN61000-4-2:2009 Level 3 EN50024:1998 Performance criteria B + A1:2001 + A2:2003