

	CS9121	CS2291
Product Picture		
Status	End-of-Sale 2023	Release 2023
Connector type	Industrial	Industrial
Processor	Intel Core i7-6822EQ 4 core (8 threads)	Intel Xeon-E 2276ML 6 cores (12 threads)
RAM	Up to 32GB	Up to 64GB
Graphics	Intel Gen 9 Graphics	Intel HD Graphics 630
Storage	1x M.2 NVME (internal)	1x M.2 NVME (internal)
Dimensions	220 x 43.4 x 365 mm (8.66 x 1.71 x 14.37 inch)	220 x 43.4 x 365 mm (8.66 x 1.71 x 14.37 inch)
Weight	4.1 kg (9 lbs)	4.1 kg (9 lbs)
Video	1x VGA 1x HDMI	1x VGA 1x HDMI
Ethernet	10x 1000Base-T 2x 1000Base-T with PoE	10x 1000Base-T 2x 1000Base-T with PoE
Serial	1x RS232* (Rx/Tx)	1x RS232* (Rx/Tx)
USB	2x USB3 2x USB2.0	2x USB3 2x USB2.0
Service	1x MilDef Service	1x MilDef Service
Power connector	ITT CA-B (ITS)	ITT CA-B (ITS)
Power	12-32V DC	12-32V DC
IP rating	IP65	IP65
Military Standards	MIL-STD-461F MIL-STD-810G MIL-STD-1275D	MIL-STD-461F MIL-STD-810G MIL-STD-1275D
Temp operating	-40°C to +55°C (-40°F to 131 °F)	-40°C to +55°C (-40°F to 131 °F)
Temp storage	-40°C to +71°C (-40°F to 160 °F)	-40°C to +71°C (-40°F to 160 °F)