

19"/2 ® ESW1127



Rugged switch in a 19"/2 ® form factor

The 19"/2 ® ESW1100 Series gives you eight high performance Ethernet ports in a compact form factor. There's no need to configure the Switch before use – simply plug in your cables and you'll have data streaming instantly.

The switch conforms to the IEEE802.3u standard for smooth integration with other devices and offers alternatives with Power over Ethernet capability and fiber interfaces. The unit is design from the ground up for defence applications, you can count on long-term performance in any environment.

Small form factor

The MilDef 19"/2 ® form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

Flexible mounting

The 19"/2 ® standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

Features

- Vitesse Switch Architecture
- Unmanaged switch
- 10-32 VDC
- Passively cooled

Connector Interfaces

DC IN (front)	• 1x Power
ETH 1-8 (front)	8 connectors which each has: <ul style="list-style-type: none"> • 1x ETH 1000BASE-T
ETH 9-10 (front)	2 connectors which each has: <ul style="list-style-type: none"> • 1x ETH 1000BASE-LX
SERVICE (back)	• 1x RS232 Service

Other Interfaces

1x Status indicator (front)

Technical Specification

LAN 1000BASE-LX	1000BASE-LX standard with SM 1310 nm fiber
LAN 1000BASE-T	1000BASE-T standard
Switch architecture	Vitesse Switch Architecture
Switch type	Unmanaged switch
Electronics ground to chassis	Isolated
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Polarity protection	Protected against incorrect polarity connection on the power input within the normal operating voltage range
Power consumption	No PoE: Max 19 W No PoE: Typ 11 W No PoE: Idle 9 W PoE: Max 143 W PoE: Typ 75 W
Power input	10-32 VDC
Power to chassis	Isolated
Power to electronics ground	Isolated
Chassis material	Aluminum
Coating and color	AE0305-6603120 Axalta (RAL 6031)
Cooling	Passively cooled
Dimensions	220 x 43.4 x 228 mm (8.66 x 1.71 x 9 in) (WxHxD)
Earth point	M6 12 mm
Surface treatment chassis	Chromit-Al
Weight	2.3 kg (5.1 lbs)
MTBF	> 260,000 h
CE	Compliant

Environmental Specification

Contamination by fluids	MIL-STD-810G, Method 504.1, Procedure II - Small Systems
Functional shock - Operating	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40 g 11 ms
Fungus	MIL-STD-810G, Method 508.6, Fungus 90 days
High temperature - Operating	MIL-STD-810G, method 501.5, Procedure II - Operation 65 °C (149 °F) (Optional 71 °C (160 °))
High temperature - Storage	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)
Humidity	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 % RH Ten 24 h cycles
IP Class (Solid Particle Protection)	IP Class 6X
IP Class (Water)	IP Class X5
Low air pressure - Rapid decompression	MIL-STD-810G, Method 500.5, Procedure III - Rapid decompression 75.2 kPa, corresponding to 2,438 m (8,000 ft) 17 kPa, corresponding to 12,192 m (40,000 ft)
Low air pressure - Operating	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4,572 m (15,000 ft)
Low temperature - Operating	MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)
Low temperature - Storage	MIL-STD-810G, method 502.5, Procedure I - Storage -40 °C (-40 °F)
Noise level	Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance
Salt fog	MIL-STD-810G Method: 509.5 5 % ± 1 % (by weight) Two cycles, 24 h wet + 24 h dry / cycle

Temperature Shock - Operating	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 71 °C (160 °F) -40 °C (-40 °F)
Transit drop, in shipping package	MIL-STD-810G, method 516.6, Procedure IV - Transit Drop. Table 516.6-VI, Transit drop test, < 45.4 kg (100 lbs), < 91 cm (36 inch), Manpacked or man-portable
Vibration - Helicopter	MIL-STD-810G. Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
Vibration - Loose cargo	MIL-STD-810G. Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
Vibration - Tracked vehicles	MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles
Vibration - Wheeled vehicles	MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles

EMC Specification

EMI conducted CE102	MIL-STD-461F, Method CE102, Conducted emissions, power leads BASIC CURVE 10 kHz - 10 MHz
EMI radiated RE102	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 2 MHz - 18 GHz
EMI radiated RE102 - extended	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 10 kHz - 2 MHz
EMS conducted CS101	MIL-STD-461F, Method CS101, Conducted susceptibility, power leads CURVE #1 30 Hz - 150 kHz
EMS conducted CS114	MIL-STD-461F, Method CS114, Conducted bulk susceptibility Army, Ground 10 kHz - 200 MHz
EMS conducted CS115	MIL-STD-461F, Method CS115, Conducted susceptibility, bulk cable injection, impulse excitation

EMS conducted CS116	MIL-STD-461F, Method CS116, Conducted susceptibility, damped sinusoidal transients, cables and power leads 10 kHz - 100 MHz
EMS radiated RS103	MIL-STD-461F, Method RS103, Radiated susceptibility, electric field Army 2 MHz - 18 GHz
ESD	EN61000-4-2:2009 Level 3 EN55024:1998 Performance criteria B + A1:2001 + A2:2003

