

19"/2 Cisco 4G Router RM6121



Router in a 19inch2 form factor

The 19"/2 RM6121 is a 4G Router based on the Cisco 809 Series. It enables connectivity to cellular networks over multimode 4G, 3G and 2G. It is fully packed with advanced Cisco networking features in a frame up to 75% smaller than standard 19" rugged routers, which significantly reduces the routers weight, energy consumption and heat production.

Mounting

The 19"/2 standard enables flexible mounting with customized brackets. The unit can be mounted in a 19" rack, half racks, directly to a surface and in any angle.

Built to take a beating

The router is built to withstand the harshest conditions over the long haul. It features aluminium casing, rugged connectors for easy integration and will operate down to -40 C.

Guaranteed performance

Our products always come with a lifetime support to ensure your equipment maintains peak performance for many missions to come. We also serve units and stock spare parts for 5 years end-of-life.

Features

- Based on the Cisco IR809G-LTE-GA-K9
- Passively cooled

19"/2 Cisco 4G Router RM6121

Connector Interfaces

MAIN (front)	• 1x Cellular Antenna
DIV (front)	• 1x Cellular Antenna
DC IN (back)	• 1x Power
FA1,FA2 (front)	2 connectors which each has: • 1x ETH 100BASE-T
FA3,FA4 (back)	2 connectors which each has: • 1x ETH 100BASE-T
GE1 (front)	• 1x ETH 1000BASE-T
GPS (front)	• 1x GPS
SERVICE (back)	• 1x RS232 Service
S0, S1 (back)	2 connectors which each has: • 1x Serial Console
CONSOLE-S (front)	• 1x Serial Console
CONSOLE-U (front)	• 1x Serial Console
USB (front)	• 1x USB 2.0

Other Interfaces

- 1x Sim Card (front)
- 1x System Button (front)

Technical Specification

Blanking	Double-pressing the System button
LAN 1000BASE-T	1000BASE-T standard
Reference Design	Based on the Cisco IR809G-LTE-GA-K9
MIL-STD-1275D	5.3.2.1 5.3.2.2 5.3.2.3 5.3.2.4
Polarity protection	Protected against polarization failure on the power input in the voltage range of normal operation.
Power input	12-32 VDC
Coating and color	Dupont AE0305-6603120 (RAL6031)
Cooling	Passively cooled
Dimensions Width and Height	220x44mm (WxH)
Earth point	M6 12mm
Rack Mounting depth	430mm
Surface treatment chassis	Chromit-Al
Weight	5 kg

Environmental Specification (* designed to meet)

Functional Shock - Operating*	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock.
-------------------------------	---

Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment
40g
11 ms

High temperature - Operating*	MIL-STD-810G, method 501.5, Procedure II - Operation 55 °C
High temperature - Storage*	MIL-STD-810G, method 501.5, Procedure I - Storage 71 °C
Humidity*	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 %rh Ten 24-hour cycles
IP Class (Solid Particle Protection)*	IP Class 6X
IP Class (Water)*	IP Class X5
Low air pressure - Rapid Decompression*	MIL-STD-810G, Method 500.5, Procedure III - Rapid Decompression 75.2kPa, corresponding to 2,438m (8.000 ft) 17kPa, corresponding to 12192m (40.000 ft)
Low air pressure - Operating*	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4572m (15.000 ft)
Low temperature - Operating*	MIL-STD-810G, method 502.5, Procedure II - Operation -40 C
Low temperature - Storage*	MIL-STD-810G, method 502.5, Procedure I - Storage -40 C
Noise level*	Maximum noise level of 40dB SPL A-weighting @ 1m distance
Salt fog*	MIL-STD-810G Method: 509.5 5% +- 1% (by weight) Two cycles, 24h wet + 24h dry /cycle
Temperature Shock - Operating*	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 C - 40 C
Transit drop, in shipping package*	MIL-STD-810G, method 516.6, Procedure IV - Transit Drop. Table 516.6-VI, Transit drop test, < 45.4 kg, < 91 cm, Manpacked or man-portable
Vibration - Helicopter*	MIL-STD-810G, Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
Vibration - Loose Cargo*	MIL-STD-810G, Method 514.6, Procedure II - Loose cargo

19"/2 Cisco 4G Router RM6121

	transportation, Category 5 - Truck/trailer - loose cargo
Vibration - Tracked Vehicles*	MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles
Vibration - Wheeled Vehicle*	MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles
EMC Specification (* designed to meet)	
CE EMI*	EN61000-6-3:2007
CE EMS*	EN55022:2010
EMI conducted CE102*	MIL-STD-461F, Method CE102 BASIC CURVE 10kHz to 10MHz
EMI radiated RE102*	MIL-STD-461F 2MHz - 18Ghz Navy Mobile & Army
EMS conducted CS101*	MIL-STD-461F, Method CS101, conducted suceptibility, power leads CURVE #1 30Hz to 150kHz
EMS conducted CS114*	MIL-STD-461F 10kHz - 200MHz Army, Ground
EMS conducted CS115*	MIL-STD-461F
EMS conducted CS116*	MIL-STD-461F 10 kHz to 100 MHz
EMS radiated RS103*	MIL-STD-461F 2MHz to 1GHz Army
ESD*	EN61000-4-2:2009 Level 3 EN50024:1998 Performance criteria B + A1:2001 + A2:2003