

DS11 Adjustable Stand CSP135



DS11 Adjustable Stand

The Adjustable Stand - which is very easy to operate - has a perfect fit for DS tablet PCs. It is adjustable in all directions, and works perfect as vehicle or wall mount. We recommend you to combine it with DockLite docking station which will enable further connection possibilities.

Guaranteed performance

Our products always come with a lifetime support to ensure your equipment maintains peak performance for many missions to come. We also serve units and stock spare parts for 5 years end-of-life.

DS11 Adjustable Stand CSP135

Technical Specification

Ease of mounting of DS11	Removable for daily use outside the holder
Fastening point of DockLite	DockLite docking station
Mounting of DS11	DS11 Tablet
Weight	2.2 kg

Environmental Specification (* designed to meet)

High temperature - Operating*	MIL-STD-810G, Method 501.5, Procedure II - Operation 55° C (131° F)
High temperature - Storage*	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)
Humidity*	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 %rh Ten 24-hour cycles
Low air pressure - Rapid Decompression*	MIL-STD-810G, Method 500.5, Procedure III - Rapid Decompression 75.2kPa, corresponding to 2,438m (8.000 ft) 17kPa, corresponding to 12192m (40.000 ft)
Low air pressure - Operating*	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4572m (15.000 ft)
Low temperature - Operating*	MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)
Low temperature - Storage*	MIL-STD-810G, method 502.5, Procedure I - Storage -40 C (-40 °F)
Temperature Shock - Operating*	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) - 40 °C (-40 °F)