

MilDef DT13



Rugged tablet with built-in keyboard

The MilDef DT13 offers a rugged 9" tablet with a powerful Intel® Core™ i7 processor and resistive multi-touch display. Designed for tactical military environments where reliability and performance are key.

and reuse customization done on previous generations.

Customizable

Are you looking for features and functions beyond the standard solutions offered by large commercial manufacturers? MilDef products are designed to enable customization to your specific program requirements, e.g. connectors, chassis modifications, mounting solutions, etc. Contact your nearest MilDef Sales Office and we will help you to find a solution that meet your requirements.

Guaranteed performance

All MilDef products come with comprehensive lifecycle sustainment support to ensure your equipment maintains peak performance for many missions to come. We also guarantee the availability of spare parts for 5 years after product end-of-life.

Features

- Intel® Core™ i7-7600
- Up to 32 GB RAM
- 9" display
- Removable M.2 SSD
- Resistive Multi-Touch Screen
- Qwerty Keyboard
- Aluminum Case
- MIL-STD-810
- MIL-STD-461
- IP65

Technical Specification

CPU	Intel® Core™ i7-7600U Processor
Display	9" WXGA (1280 x 768) Brightness: 850 nits (typical)
Touch screen	Resistive Multi-Touch Screen
Invisible Mode On/Off	Yes
Case	Magnesium alloy

Software

Operating system	Windows 10
------------------	------------

Memory

RAM	Up to 32 GB DDR4 2133 MHz
Storage	M.2 2280 SATAIII SSD (removable)

Keyboard

Qwerty keyboard	Layout: Norwegian, Nordic or US***
-----------------	---------------------------------------

Graphics

GPU	Intel® UHD Graphics 620
-----	-------------------------

Battery

Primary	10.8 V / 5800 mAh Li-Ion
Secondary	10.8 V / 8700 mAh Li-Ion <i>optional</i>

Sound

Audio	HD Audio
-------	----------

Security & Management

TPM	TPM2.0
-----	--------

Interfaces

Ethernet	1x Ethernet 1000Base-T (second Ethernet via docking connector)
WiFi/Bluetooth	802.11 a/b/g/n/ac <i>optional</i> Bluetooth 5.0 <i>optional</i>
GPS/GLONASS	Ublox Neo-M8N <i>optional</i>
USB (Type A)	1x USB 3.1 Gen 1 (w. fast charging) 1x USB 3.1 Gen 1
USB (Type C)	1x USB 3.1 Gen 1
Express card slot	Yes
SIM card slot	Yes
SD card slot	Yes
Docking port	Yes
Speaker	Stereo Speakers
Serial	1x COM*
Function buttons	- 4 function keys (F1-F4) - Power button - Minus (-) & plus (+) sign - Arrow keys - Function Backlight - Esc, Ctrl, Alt, Del, Fn & Enter - Brightness

Technical Specification (cont.)

Size & Weight

Dimensions with bumpers (W x D x H)	259 x 199 x 49.2 mm (10.2 x 7.8 x 1.9 Inch)
Weight	~ 2.7 kg (5.9 lbs) depending configuration

Temperature Range

Operational DC	-30° C + 50° C (-22° F to +122° F)
----------------	------------------------------------

Operational Battery Storage	Battery is charging between 0° C to +45° C (+32° F to +113° F)** -10° C to +55° C (+14° F to +131° F) -40° C to +71° C (-40° F to +160° F)
-----------------------------	--

Reliability

MTBF (Ground Benign)	61 484 hours
MTTR	11.805 minutes

Power

Power input	12- 32 V _{DC} (including surge protector & polarity protection)
Operating time	5 hours
Power consumption	Idle: 17 W Max: 90 W
AC Adapter	Please see the accessories section

Standards

CE / FCC	Yes / Yes
REACH	Yes
Environment	MIL-STD-810G IP65
EMC/EMI	MIL-STD-461G Ground Army

Warranty

Warranty	5 years
----------	---------

Customization

Need anything not included in the data sheet? MilDef products are designed to enable customization to your specific program requirements. Please contact your MilDef sales team member to find the best solution for your requirements.

* Can be selected via BIOS RS232/RS422/RS485

**Secondary battery operating battery: -10°C to +55°C (+14°F to +131°F)

*** Other languages available at request



Accessories & Options

AC/DC Adapters

AC Adapter 90W (EU) – Indoor Use	110/220 V _{AC} (100~240 V _{AC}), 50/60 Hz
AC Adapter 90W (US) – Indoor Use	110/220 V _{AC} (100~240 V _{AC}), 50/60 Hz
AC Adapter 90W Ground Army – Indoor Use (EU)	110/220 V _{AC} (100~240 V _{AC}), 50/60 Hz
AC Adapter 90W Ground Army – Indoor Use (US)	110/220 V _{AC} (100~240 V _{AC}), 50/60 Hz
AC90 – AC adapter 90W Ground Navy (IP65, MIL-STD-810G, MIL-STD-461F & Wide temp)	110/220 V _{AC} (90~264 V _{AC}), 50/60 Hz or 400Hz
AC90 – AC adapter 90W Ground Army (IP65, MIL-STD-810G, MIL-STD-461F & Wide temp)	110/220 V _{AC} (90~264 V _{AC}), 50/60 Hz or 400Hz

Charger

Multi battery charger	Charges up to two primary and two secondary battery.
-----------------------	--

Mounting & Transport

Docking and mounting solutions	Please get in contact with your MilDef sales office for options
Bag / Backpack	Please get in contact with your MilDef sales office for options

Operating system

Windows 10



Environmental Specification

Low Air pressure

Low air pressure – Rapid Decompression MIL-STD-810H, Method 500.6, <i>Procedure I - Storage/Air Transport</i>	12.192 m / 40.000 ft
Low air pressure - Operating MIL-STD-810H, Method 500.6, <i>Procedure II - Operation/Air Carriage</i>	4.572 m / 15.000 ft

IP Class

IP	IP65
----	------

Freeze/Thaw

Freeze/Thaw – Operational MIL-STD-810H, Method 524.1 <i>Procedure III - Rapid Temperature Change</i>	According to method and procedure
--	-----------------------------------

Humidity

Humidity – Storage MIL-STD-810H, Method 507.6 <i>Procedure II (Aggravated) - Figure 507.6-7</i>	24-hours per cycle / Total of 10 cycles Between 30° C (86° F) and 60° C (140° F) with the relative humidity at 95% constant
---	---

Rain

Rain – Operating MIL-STD-810H, Method 506.6 <i>Procedure II</i>	276 kPa(40psig) 5-surfaces 40-minutes/surface
---	---

Shock

Functional Shock - Operating MIL-STD-810H, Method 516.8 <i>Procedure I - Figure 516.8-IV</i>	Table 516.7-IV Terminal-peak sawtooth shock pulse 40 g, 11 ms
--	---

Salt Fog

Salt fog MIL-STD-810H Method 509.7	5 % +- 1 % (by weight) 24 h wet + 24 h dry /cycle Total 2 cycles / 96 hours
---------------------------------------	---

Temperature

Low temperature - Operating MIL-STD-810H Method 502.7 <i>Procedure II – Operation</i>	-20° C / -4° F (optional -30° C / -22° F)
Low temperature - Storage MIL-STD-810H Method 502.7 <i>Procedure I – Storage</i>	-40° C / -40° F
High temperature - Operating MIL-STD-810H Method 501.7 <i>Procedure II – Operation</i>	50° C / 122° F
High temperature - Storage MIL-STD-810H Method 501.7 <i>Procedure I – Storage</i>	71° C / 160° F
Temperature Shock – Non-Operating MIL-STD 810H Method 503.7 <i>Procedure I-C (Figure 503.7-3)</i>	-40° C / -40° F to 71° C / 160° F

Vibrations

Vibration - Operational MIL-STD-810H, Method 514.8 <i>Category 20 - Ground Vehicles-ground mobile</i>	Table 514.8C-VII Composite wheeled vehicle vibration exposure Figure 514.8C-6, 60-minutes/axis
Vibration Storage MIL-STD-810H, Method 514.8 <i>Category 24 - General minimal integrity</i>	60-minutes/axis



EMC Specification

MIL-STD-461G

MIL-STD-461G, Method CE101	Conducted Emissions, Power Leads 30 Hz to 150 kHz
MIL-STD-461G, Method CE102	Conducted Emissions, Power Leads 10 kHz to 10 MHz
MIL-STD-461G, Method CS101	Conducted susceptibility, power leads 30 Hz to 150 kHz Curve #1
MIL-STD-461G, Method CS114	Bulk Cable Injection 10 kHz to 200 MHz
MIL-STD-461G, Method CS115	Conducted susceptibility, bulk cable injection, impulse excitation
MIL-STD-461G, Method CS116	Conducted Susceptibility, Damp Sinusoidal Transients, Cables and Power Leads, 10 kHz to 100 MHz
MIL-STD-461G, Method CS118	Personnel borne electrostatic discharge – All (ESD)
MIL-STD-461G, Method RE101	Radiated Emissions, Magnetic Field 30 Hz to 100 kHz
MIL-STD-461G, Method RE102	Radiated Emissions, Electric Field 10 kHz to 18 GHz
MIL-STD-461G, Method RS101	Radiated Susceptibility, Magnetic Field 30 Hz to 100 kHz
MIL-STD-461G, Method RS103	Radiated Susceptibility, Electric Field 2 MHz ~ 18 GHz