

# 19"/2® RM2115



## Cisco router in a 19"/2® form factor

The 19"/2® RM2115 Series is a high-performance router based on the Cisco ESR6300 router card running Cisco IOS® XE. It comes with onboard hardware encryption, which enables highly secure video, voice and data services. The router offers four 1G copper LAN, one copper WAN and one fiber WAN.

### Small form factor

The MilDef 19"/2® form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

### Flexible mounting

The 19"/2® standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

### Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging

electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

### Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

### Features

- Based on Cisco ESR6300
- Cisco IOS® XE
- IPv4 and IPv6 unicast and multicast routing
- Unified Communications Manager Express support
- Firewall support

**Connector Interfaces**

<b>SERVICE</b> (back)	• 1x RS232 Service
<b>X1 DC IN</b> (front)	• 1x Power
<b>X2</b> (front)	• 1x ETH 1000BASE-T LAN1 • 1x ETH 1000BASE-T LAN2
<b>X3</b> (front)	• 1x ETH 1000BASE-T LAN4
<b>X4</b> (front)	• 1x ETH 1000BASE-T LAN3
<b>X5</b> (front)	• 1x Cisco Serial Console
<b>X6</b> (front)	• 1x 100BASE-LX WAN1
<b>X7</b> (back)	• 1x ETH 1000BASE-T WAN2

**Other Interfaces**

1x System button (front)

**Technical Specification**

<b>Blanking</b>	Enable/disable all externally visible indicators from emitting light via the "blanking command"
<b>Cisco IOS XE software</b>	ESR6300 Network Essentials or Network Advantage Default (50 Mbps) Performance (250 Mbps) Boost (2 Gbps) Optional licenses for CME, Cisco DNA Center and HSEC
<b>Factory reset</b>	Factory reset by service command
<b>Firewall</b>	Zone-based policy firewall Stateful inspection Advanced application inspection and control HTTPS/FTP/Telnet Authentication Proxy Dynamic and static port security Firewall stateful failover VRF-aware firewall
<b>LAN 1000BASE-T</b>	1000BASE-T standard
<b>LAN 100BASE-LX</b>	100BASE-LX standard with SM 1310 nm

**Management**

Web UI  
MIB  
SmartPort  
SNMP  
Syslog  
DHCP server  
SPAN session  
Full Flexible Netflow (FnF)  
RADIUS  
HSRP

**Reference design**

Based on the Cisco ESR6300

**Router features**

GRE and MGRE  
802.1D STP  
NAT  
DDNS  
IPv4 and IPv6 Multicast  
OSPF, BGP, EIGRP, RIP v1-v2  
L2TP  
VPN for remote access  
IPSec over IPv6  
Cisco IOS Firewall  
2 routed and 4 switched Gigabit Ethernet interfaces

**Security**

SSL VPN  
NGE  
PKI support  
IPSEC  
IPSEC stateful failover  
VRF-aware IPSEC  
Easy VPN  
DMVPN  
Flex VPN  
SSHv2  
MACsec  
Port security  
802.1x  
DHCP snooping  
Dynamic ARP inspection  
IP source guard  
Guest VLAN  
MAC authentication bypass  
802.1x multidomain authentication  
Storm control  
SCP  
SNMPv3  
TACACS+  
RADIUS server/client  
Integrated Threat Control (CoPP, etc)

**Electronics ground to chassis**

Isolated

**MIL-STD-1275E**

Fully compliant

**Polarity protection**

Protected against incorrect polarity connection on the power input within the normal operating voltage range

**Power consumption**

Max: 11 W  
Idle: 8.5 W

<b>Power input</b>	12-32 VDC
<b>Power to chassis</b>	Isolated
<b>Power to electronics ground</b>	Isolated
<b>Chassis material</b>	Aluminum
<b>Coating and color</b>	AE0305-6603120 Axalta (RAL 6031)
<b>Cooling</b>	Passively cooled
<b>Depth</b>	279 mm (11 in)
<b>Dimensions width and height</b>	220 x 43.4 mm (8.66 x 1.71 in) (WxH)
<b>Earth point</b>	M6 12 mm
<b>Rack mounting depth</b>	400 mm (15.8 in)
<b>Surface treatment chassis</b>	Chromit-Al
<b>Weight</b>	2.5 kg (5.6 lbs)
<b>MTBF</b>	125,000 h
<b>CE</b>	Compliant

### Environmental Specification

<b>Functional shock - Operating</b>	MIL-STD-810H, Method 516.8, Procedure I - Functional shock. Table 516.8-IV, Terminal peak sawtooth pulse, Ground materiel 40 g 11 ms
<b>High temperature - Operating</b>	MIL-STD-810H, Method 501.7, Procedure II - Operation 65 °C (149 °F) (Optional 71 °C (160 °))
<b>High temperature - Storage</b>	MIL-STD-810H, Method 501.7, Procedure I - Storage 71 °C (160 °F)
<b>Humidity</b>	MIL-STD-810H, Method 507.6, Procedure II - Aggravated 95 ± 4% RH Ten 24-hour cycles
<b>IP Class (Solid Particle Protection)</b>	IP Class 6X
<b>IP Class (Water)</b>	IP Class X5
<b>Low air pressure - Rapid decompression</b>	MIL-STD-810H, Method 500.6, Procedure III - Rapid decompression 2,438 m (8,000 ft) 12,192 m (40,000 ft)
<b>Low air pressure - Operating</b>	MIL-STD-810H, Method 500.6, Procedure II - Operation/air carriage 4,572 m (15,000 ft)
<b>Low temperature - Operating</b>	MIL-STD-810H, Method 502.7, Procedure II - Operation -40 °C (-40 °F)

<b>Low temperature - Storage</b>	MIL-STD-810H, Method 502.7, Procedure I - Storage -40 °C (-40 °F)
<b>Noise level</b>	Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance
<b>Salt fog</b>	MIL-STD-810H, Method 509.7 5 ± 1% (by weight) Two cycles, 24 h wet + 24 h dry / cycle
<b>Temperature shock - Operating</b>	MIL-STD 810H, Method 503.7, Procedure I-C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) -40 °C (-40 °F)
<b>Vibration - Helicopter</b>	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
<b>Vibration - Loose cargo</b>	MIL-STD-810H, Method 514.8, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
<b>Vibration - Tracked vehicle</b>	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 20 - Ground vehicle - ground mobile, Tracked vehicle
<b>Vibration - Wheeled vehicle</b>	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 20 - Ground vehicle - ground mobile, Wheeled vehicle

### EMC Specification

<b>EMI conducted CE102</b>	MIL-STD-461F, Method CE102, Conducted emissions, power leads BASIC CURVE 10 kHz - 10 MHz
<b>EMI radiated RE102</b>	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 2 MHz - 18 GHz
<b>EMS conducted CS101</b>	MIL-STD-461F, Method CS101, Conducted susceptibility, power leads CURVE #1 30 Hz - 150 kHz
<b>EMS conducted CS114</b>	MIL-STD-461F, Method CS114, Conducted bulk susceptibility Army, Ground 10 kHz - 200 MHz
<b>EMS conducted CS115</b>	MIL-STD-461F, Method CS115, Conducted susceptibility, bulk cable injection, impulse excitation

EMS conducted CS116	MIL-STD-461F, Method CS116, Conducted susceptibility, damped sinusoidal transients, cables and power leads 10 kHz - 100 MHz
EMS radiated RS103	MIL-STD-461F, Method RS103, Radiated susceptibility, electric field Army 2 MHz - 1 GHz

