

19"/2® CS2271



Computer in a 19"/2® form factor

The CS2200 gives you a reliable, high-performance computer in the 19"/2 form factor that is optimized for low Size, Weight and Power (SWaP) to meet military requirements without sacrificing reliability, ruggedness or performance.

Small form factor

The MilDef 19"/2® form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

Flexible mounting

The 19"/2® standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally

proven, MilDef products are actively employed in military operations in over 60 countries.

Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

Features

- Up to 64 GB RAM ECC
- RAID 0, 1, 5 with supercap cache module
- 80 mm axial fan
- 2.8 GHz, Intel® Xeon® 9th Gen, E-2276ME
- 12-36 VDC
- Fan cooled (optional fanless with reduced performance)

Connector Interfaces

DC IN (front)	• 1x Power
FAN (back)	• 1x FAN
SERVICE (back)	• 1x RS232 Service
X1 (front)	• 1x VGA • 1x AUDIO_IN • 1x AUDIO_OUT • 2x USB • 1x RS232
X2 (front)	• 4x ETH • 1x USB
X3 (front)	• 1x DVI • 3x USB • 1x Remote Power On • 2x RS232

Other Interfaces

3x MilDef Disk Slot (front)
1x System button (front)

Technical Specification

Blanking	Double-pressing the System button
Computer memory	Up to 64 GB RAM ECC
Computer storage	RAID 0, 1, 5 with supercap cache module
Fan	80 mm axial fan
LAN 1000BASE-T	1000BASE-T standard
Processor	2.8 GHz, Intel® Xeon® 9th Gen, E-2276ME 6 cores, 12 threads
Electronics ground to chassis	Isolated
MIL-STD-1275E	Fully compliant
Polarity protection	Protected against incorrect polarity connection on the power input within the normal operating voltage range
Power consumption	135 W (with heater)
Power input	12-36 VDC
Power to chassis	Isolated
Power to electronics ground	Isolated
Chassis material	Aluminum
Coating and color	AE0305-6603120 Axalta (RAL 6031)
Cooling	Fan cooled (optional fanless with reduced performance)
Earth point	M6 12 mm
Surface treatment chassis	Chromit-Al

Weight 7.5 kg (16.5 lbs) with disks

MTBF > 25,000 h

CE Compliant

Environmental Specification

Functional shock - Operating MIL-STD-810H, Method 516.8, Procedure I - Functional shock. Table 516.8-IV, Terminal peak sawtooth pulse, Ground material 40 g 11 ms

High temperature - Operating MIL-STD-810H, Method 501.7, Procedure II - Operation 55 °C (131 °F)

High temperature - Storage MIL-STD-810H, Method 501.7, Procedure I - Storage 71 °C (160 °F)

Humidity MIL-STD-810H, Method 507.6, Procedure II - Aggravated 95 ± 4% RH Ten 24-hour cycles

IP Class (Solid Particle Protection) IP Class 6X

IP Class (Water) IP Class X5

Low air pressure - Rapid decompression MIL-STD-810H, Method 500.6, Procedure III - Rapid decompression 2,438 m (8,000 ft) 12,192 m (40,000 ft)

Low air pressure - Operating MIL-STD-810H, Method 500.6, Procedure II - Operation/air carriage 4,572 m (15,000 ft)

Low temperature - Operating MIL-STD-810H, Method 502.7, Procedure II - Operation -40 °C (-40 °F)

Low temperature - Storage MIL-STD-810H, Method 502.7, Procedure I - Storage -40 °C (-40 °F)

Noise level Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance

Salt fog MIL-STD-810H, Method 509.7 5 ± 1% (by weight) Two cycles, 24 h wet + 24 h dry / cycle

Temperature shock - Operating MIL-STD 810H, Method 503.7, Procedure I-C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) -40 °C (-40 °F)

Vibration - Helicopter	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
Vibration - Loose cargo	MIL-STD-810H, Method 514.8, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
Vibration - Tracked vehicle	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 20 - Ground vehicle - ground mobile, Tracked vehicle
Vibration - Wheeled vehicle	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 20 - Ground vehicle - ground mobile, Wheeled vehicle

EMC Specification

EMI conducted CE102	MIL-STD-461F, Method CE102, Conducted emissions, power leads BASIC CURVE 10 kHz - 10 MHz
EMI radiated RE102	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 2 MHz - 18 GHz
EMS conducted CS101	MIL-STD-461F, Method CS101, Conducted susceptibility, power leads CURVE #1 30 Hz - 150 kHz
EMS conducted CS114	MIL-STD-461F, Method CS114, Conducted bulk susceptibility Army, Ground 10 kHz - 200 MHz
EMS conducted CS115	MIL-STD-461F, Method CS115, Conducted susceptibility, bulk cable injection, impulse excitation
EMS conducted CS116	MIL-STD-461F, Method CS116, Conducted susceptibility, damped sinusoidal transients, cables and power leads 10 kHz - 100 MHz
EMS radiated RS103	MIL-STD-461F, Method RS103, Radiated susceptibility, electric field Army 2 MHz - 1 GHz
ESD	EN61000-4-2:2009 Level 3 EN55024:1998 Performance criteria B + A1:2001 + A2:2003