

USB to RJ45 network adapter - Concept 3408



MilDef offers our customers complete realization of any product idea or concept within rugged electronics. Based on our long experience of designing and customizing products, our engineering team is ready to attack any technical problem thrown at them. A MilDef concept enables the possible implementation of customer specific requirements. Realization may involve NRE cost. This featured product is currently at a concept stage, contact us to further discuss your requirements.

The Network adapter converts USB 2.0 to RJ45 10/100/1000Base-T.

Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

Customizable

Are you looking for additional features and functions? MilDef specializes in customized solutions, to include change of connectors, chassis modifications, mounting solutions, etc. Contact your nearest MilDef Sales Office

and we will help you tailor a solution to meet your exact requirements.

Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

Features

- MIL-STD-810 and MIL-STD-461 compliant
- Low power, size and weight
- Bottom mounting holes
- Industrial connectors

USB to RJ45 network adapter - Concept 3408

Connector Interfaces

ETH (front)	• 1x ETH 1000BASE-T
USB (back)	• 1x USB 2.0

Technical Specification

Power consumption	1.5 W
Power input USB	USB 5 VDC
Chassis material	Aluminum
Coating and color	Dupont AE0305-6603120 (RAL6031)
Cooling	Passively cooled
Dimensions	55 x 30 x 100 mm (2.2 x 1.2 x 4 in) (WxHxD)
Surface treatment chassis	Chromit-Al
Weight	0.3 kg (0.7 lbs)
MTBF	Greater than 25,000 h
CE	Compliant

Environmental Specification

Functional shock - Operating	MIL-STD-810H, Method 516.8, Procedure I - Functional Shock. Table 516.8-IV, Terminal peak sawtooth pulse, Ground Materiel 40 g 11 ms
High temperature - Operating	MIL-STD-810H, Method 501.7, Procedure II - Operation 60 °C (140 °F)
High temperature - Storage	MIL-STD-810H, Method 501.7, Procedure I - Storage 71 °C (160 °F)
Humidity	MIL-STD-810H, Method 507.6, Procedure II - Aggravated 95 ± 4% RH Ten 24-hour cycles
IP Class (Solid Particle Protection)	IP Class 6X
IP Class (Water)	IP Class X5
Low air pressure - Rapid decompression	MIL-STD-810H, Method 500.6, Procedure III - Rapid Decompression 2,438 m (8,000 ft) 12,192 m (40,000 ft)
Low air pressure - Operating	MIL-STD-810H, Method 500.6, Procedure II - Operation/Air Carriage 4,572 m (15,000 ft)
Low temperature - Operating	MIL-STD-810H, Method 502.7, Procedure II - Operation -40 °C (-40 °F)
Low temperature - Storage	MIL-STD-810H, Method 502.7, Procedure I - Storage -40 °C (-40 °F)

Noise level	Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance
Salt fog	MIL-STD-810H, Method 509.7 5 ± 1% (by weight) Two cycles, 24 h wet + 24h dry / cycle
Temperature shock - Operating	MIL-STD 810H, Method 503.7, Procedure I-C, - Multi-Cycle Shocks from Constant Extreme Temperature 55 °C (131 °F) -40 °C (-40 °F)
Vibration - Helicopter	MIL-STD-810H, Method 514.8, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter
Vibration - Loose Cargo	MIL-STD-810H, Method 514.8, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo
Vibration - Tracked Vehicles	MIL-STD-810H, Method 514.8, Procedure I - General Vibration, Category 20 - Ground vehicles - ground mobile, Tracked vehicles
Vibration - Wheeled Vehicle	MIL-STD-810H, Method 514.8, Procedure I - General Vibration, Category 20 - Ground vehicles - ground mobile, Wheeled vehicles

EMC Specification

EMI conducted CE102	MIL-STD-461F, Method CE102 BASIC CURVE 10 kHz to 10 MHz
EMI radiated RE102	MIL-STD-461F Navy Mobile & Army 2 MHz - 18 GHz
EMS conducted CS101	MIL-STD-461F, Method CS101, conducted susceptibility, power leads. CURVE #1 30 Hz to 150 kHz
EMS conducted CS114	MIL-STD-461F Army, Ground 10 kHz - 200 MHz
EMS conducted CS115	MIL-STD-461F Conducted susceptibility, bulk cable injection, impulse excitation
EMS conducted CS116	MIL-STD-461F 10 kHz - 100 MHz
EMS radiated RS103	MIL-STD-461F Army 2 MHz - 1 GHz