

MilDef DH8



MilDef DH8

A fully rugged handheld device, where performance and long-lasting operation in demanding environments are key. MilDef DH8 are made to last longer and to be supported long after your ordinary commercial handheld unit have reached its end of life.

Customizable

Are you looking for features and functions beyond the standard solutions offered by large commercial manufacturers? MilDef products are designed to enable customization to your specific program requirements e.g., connectors, chassis modifications, mounting solutions, etc. Contact your nearest MilDef Sales Office and we will help you to find a solution that meets your requirements.

Guaranteed performance

All MilDef products come with comprehensive lifecycle sustainment support to ensure your equipment maintains peak performance for many missions to come. We also guarantee the availability of spare parts for 5 years after product end-of-life.

Features

- Intel® Atom™ x6211E
- Up to 32 GB RAM
- 5.7" display
- Resistive multitouch
- Docking connector
- Water and dust resistant (IP65)
- Hot swappable batteries

Technical Specification	
CPU	Intel® Atom™ x6211E (1.5M Cache, up to 3 GHz)
Display	5.7" HD LCD (1280 x 720) Brightness: 640 nits (typical) Resistive multi touch
Case	CNC milled Aluminum
Software	
Operating system	Windows 10/11
Memory	
RAM	Up to 32 GB DDR4 (1x SO-DIMM slot)
Storage	1 x m.2 2242 SATA III SSD 256GB/512GB/1TB
Graphics	
GPU	Intel® UHD Graphics
Battery	
Battery	2x 7,2V / 2700 mAh Li-Ion (Hot swappable)
Sound	
Audio	HD Audio and Stereo Speakers
Security & Management	
TPM	TPM2.0
Secure Boot	Supported
Interfaces	
Wi-Fi/Bluetooth	Intel® AX210 Wi-Fi 6 optional Bluetooth 5.3 optional
GNSS	Ublox Neo-M9N optional (GPS/GLONASS/Galileo/BeiDou/QZSS)
USB	1x USB 3.2 Gen 2 Type C (Data transfer, Display Port, Power Delivery 3.0)
Docking port	Yes, POGO-pin
Mic	Embedded Digital Mic optional
Keypad	1 st layer: FN Lock, A1, A2, WIN, Rotation, Input Lock, Power 2 nd layer: ESC, F2, Enter, →, ↓
Optional: Military Fischer Connectors	Up to three features listed below <ul style="list-style-type: none"> - Audio - Serial (RS232/RS422/RS485)* - GLAN - USB2.0

*Only one serial protocol can be used at a time. Selectable via BIOS.

Technical Specification (cont.)	
Size & Weight	
Dimensions with bumpers (W x D x H)	201 x 99 x 44.5 mm (7.9 x 3.9 x 1.75 inch)
Weight	~ 905 g (1.99 lbs.)
Temperature Range	
Operational DC	-20°C to +60°C (-4°F to +140°F) -30°C to +60°C (-22°F to +140°F) optional
Storage	-40°C to +71° (-40°F to +160°F)
Power	
Operating time	~6 hours (depends on use of the device)
DC-in	Via USB-C connector with PD 3.0
AC Adapter	60W USB-C AC Adapter (AC-in 100-240V 50/60Hz, DC-out: 20V/3A)
Common options	
Wi-Fi 6 / Bluetooth	Military Fischer connectors
GNSS	Protection Film
Embedded digital Mic	MIL-STD-461G Ground Army
Invisible mode	Wide temperature -30°C +60°C
IP67	
Standards	
CE / FCC / UKCA	Yes / Yes / Yes
REACH / RoHS2.0	Yes / Yes
Environment	MIL-STD-810H IP65 IP67 optional
EMC/EMI	MIL-STD-461G Ground Navy optional MIL-STD-461G Ground Army optional
Warranty	
Warranty	5 years

Customization
Need anything not included in the data sheet? MilDef products are designed to enable customization to your specific program requirements. Please contact your MilDef sales team member to find the best solution for your requirements.