

KBD1104



KBD1100 Series

The KBD1100 Series is a rugged keyboard, manufactured from milled aluminum and designed for tactical military environments, where reliability and performance are key. The keyboard is designed for console mounting and is equipped with a built-in 38 mm trackball pointing device.

Customizable

Are you looking for features and functions beyond the standard solutions offered by large commercial manufacturers? MilDef products are designed to enable customization to your specific program requirements, e.g. connectors, chassis modifications, mounting solutions, etc. Contact your nearest MilDef Sales Office and we will help you find a solution that meets your requirements.

Guaranteed performance

All MilDef products come with comprehensive lifecycle sustainment support to ensure your equipment maintains peak performance for many missions to come. We also guarantee the availability of spare parts for 5 years after product end-of-life.

Key features

- 83 key Nordic Keyboard
- Switch between two USB sources via buttons
- Integrated ergonomic trackball mouse with buttons and scroll wheel
- MIL-STD-810G
- MIL-STD-461F
- IP65

Connector Interfaces

(right side) • 2x USB2.0

Other Interfaces

2x Input select button (front)

1x Keyboard with backlight (front)

1x Ergonomic trackball mouse (front)

3x Keyboard indicator (front)

Technical Specification

General functionality	USB HID 83 key keyboard with trackball mouse
Source switching	Switching between two sources
Power consumption	1 W
Power input	5 VDC
Chassis material	Aluminum
Coating and color	Dupont AE0305-1101320 (RAL 1013)
Surface treatment chassis	Chromit-Al
Weight	3 kg (6.7 lbs)
MTBF	32,930 h
CE	Compliant

Environmental Specification

Functional shock - Operating	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40 g 11 ms
High temperature - Operating	MIL-STD-810G, Method 501.5, Procedure II - Operation 55 °C (131 °F)
High temperature - Storage	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)
Humidity	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 % RH Ten 24 h cycles
IP Class (Solid Particle Protection)	IP Class 6X
IP Class (Water)	IP Class X5
Low air pressure - Rapid decompression	MIL-STD-810G, Method 500.5, Procedure III - Rapid decompression 75.2 kPa, corresponding to 2,438 m (8,000 ft) 17 kPa, corresponding to 12,192 m (40,000 ft)

Low air pressure - Operating	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4,572 m (15,000 ft)
Low temperature - Operating	MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)
Low temperature - Storage	MIL-STD-810G, method 502.5, Procedure I - Storage -40 °C (-40 °F)
Salt fog	MIL-STD-810G Method: 509.5 5 % ± 1 % (by weight) Two cycles, 24 h wet + 24 h dry / cycle
Temperature shock - Operating	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) -30 °C (-22 °F)

EMC Specification

EMI radiated RE102	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 2 MHz - 18 GHz
---------------------------	--