

Model Comparison MC700 Series



	MC701	MC702	MC703	MC704	MC705	MC706	MC708	MC709	MC710	MC711	MC712	MC714	MC715	MC717	MC718	MC719	MC720
Picture																	
Form factor	19"/6	19"/6	19"/6	19"/6	19"/6	19"/6	19"/4	19"/6	19"/4	19"/6	19"/4	19"/6	19"/6	19"/6	19"/6	19"/4	19"/6
Interface A-side	1000Base-LX SM 1310nm	1000Base-LX SM 1310nm	1000Base-FX MM 1300nm	1000BASE-SX MM 850nm	1000BASE-SX MM 850nm	1000BASE-SX MM 850nm	100 /1000 Mbps* MM 850nm	E1 interface (RJ45)	1000BASE-SX MM 850nm	1000Base-FX MM 1300nm	1000Base-LX SM 1310nm	1000BASE-SX MM 850nm	Depending on SFP module installed	1000Base-FX MM 1300nm	1000Base-LX SM 1310nm	1000Base-LX SM 1310nm	1000Base-FX MM 1300nm (OM1)
Connector A-side	PRO BEAM® mini	LC	LC	PRO BEAM® mini	LC	HMC	HMC	RJ45	HMC	LC	PRO BEAM®mini	HMC	Module dependent	HMC	Fibreco Junior	38999	LC
Interface B - side	1000Base-T	1000Base-T	1000Base-T	1000Base-T	1000Base-T	1000Base-T	100/1000 Mbps* SM 1310nm	1000Base-T	1000Base-T	1000BASE-LX SM 1310nm	1000Base-SX MM 850nm	1000Base-T	1000Base-T	1000Base-T	1000Base-T	1000Base-T	1000Base-T
Connector B-side	RJ45	RJ45	RJ45	RJ45	RJ45	RJ45	HMC	RJ45	RJ45	LC	PRO BEAM® mini	ODU	RJ45	ODU	ODU	38999	RJ45
Power In	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC	10-32V DC
Power in connector	ITS	ITS	ITS	ITS	ITS	ITS	ITS	ITS	ITS	ITS	ITS	ITS	ITS	38999	38999	ITS	ITS
Power in (USB)	5V DC	5V DC	5V DC	5V DC	5V DC	5V DC	-	5V DC	5V DC	5V DC	-	5V DC	-	5V DC	5V DC	-	5V DC
Power in (USB) connector	Binder	Binder	Binder	Binder	Binder	Binder	-	Binder	Binder	Binder	-	Binder	-	Binder	Binder	-	Binder
Other	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-	-

* Speed must be the same on both interfaces