

19"/6 MC714



Rugged ethernet media converter

The MC714 converts between gigabit multimode fiber and copper ethernet.

Small form factor

The MilDef 19"/2 ® form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

Flexible mounting

The 19"/2 ® standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

Connector Interfaces

5V DC (front)	• 1x USB 2.0
X1 DC IN (front)	• 1x Power
X2 (front)	• 1x ETH 1000BASE-T
X3 (back)	• 1x ETH 1000BASE-SX

Other Interfaces

1x Status indicator (front)

Technical Specification

Blanking	Enable/disable all externally visible indicators from emitting light via the "blanking command"
Fiber characteristics	MM 850 nm
LAN 1000BASE-SX	1000BASE-SX standard
LAN 1000BASE-T	1000BASE-T standard
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Power consumption	5 W
Chassis material	Aluminum
Coating and color	AE0305-6603120 Axalta (RAL 6031)
Cooling	Passively cooled
Dimensions	73 x 44 x 147 mm (2.9 x 1.8 x 5.8 in) (WxHxD)
Earth point	M6 12 mm
Surface treatment chassis	Chromit-Al
Weight	0.7 kg (1.6 lbs)
MTBF	> 800,000 h
CE	Compliant

Environmental Specification

Functional shock - Operating	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40 g 11 ms
High temperature - Operating	MIL-STD-810G, Method 501.5, Procedure II - Operation 55 °C (131 °F)
High temperature - Storage	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)
Humidity	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 % RH Ten 24 h cycles

IP Class (Solid Particle Protection)

IP Class 6X

IP Class (Water)

IP Class X5

Low air pressure - Rapid decompressionMIL-STD-810G, Method 500.5, Procedure III - Rapid decompression
75.2 kPa, corresponding to 2,438 m (8,000 ft)
17 kPa, corresponding to 12,192 m (40,000 ft)**Low air pressure - Operating**MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage
4,572 m (15,000 ft)**Low temperature - Operating**MIL-STD-810G, method 502.5, Procedure II - Operation
-40 °C (-40 °F)**Low temperature - Storage**MIL-STD-810G, method 502.5, Procedure I - Storage
-40 °C (-40 °F)**Noise level**

Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance

Salt fogMIL-STD-810G Method: 509.5
5 % ± 1 % (by weight)
Two cycles, 24 h wet + 24 h dry / cycle**Temperature shock - Operating**MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature
55 °C (131 °F)
-40 °C (-40 °F)**Transit drop, in shipping package**

MIL-STD-810G, method 516.6, Procedure IV - Transit Drop. Table 516.6-VI, Transit drop test, < 45.4 kg (100 lbs), < 91 cm (36 inch), Manpacked or man-portable

Vibration - Helicopter

MIL-STD-810G. Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter

Vibration - Loose cargo

MIL-STD-810G. Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo

Vibration - Tracked vehicles

MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles

Vibration - Wheeled vehicles

MIL-STD-810G. Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles

EMC Specification	
EMI conducted CE102	MIL-STD-461F, Method CE102, Conducted emissions, power leads BASIC CURVE 10 kHz - 10 MHz
EMI radiated RE102	MIL-STD-461F, Method RE102, Radiated emissions, electric field Navy Mobile & Army 2 MHz - 18 GHz
EMS conducted CS101	MIL-STD-461F, Method CS101, Conducted susceptibility, power leads CURVE #1 30 Hz - 150 kHz
EMS conducted CS114	MIL-STD-461F, Method CS114, Conducted bulk susceptibility Army, Ground 10 kHz - 200 MHz
EMS conducted CS115	MIL-STD-461F, Method CS115, Conducted susceptibility, bulk cable injection, impulse excitation
EMS conducted CS116	MIL-STD-461F, Method CS116, Conducted susceptibility, damped sinusoidal transients, cables and power leads 10 kHz - 100 MHz
EMS radiated RS103	MIL-STD-461F, Method RS103, Radiated susceptibility, electric field Army 2 MHz - 1 GHz

