

# 19"/6 MC720



## Mediaconverter in a 19"/6 form factor

The MC720 is a rugged mediaconverter for converting RJ45 copper Ethernet to 100BAE-FX 1300 nm OM1 LC fiber.

### Small form factor

The MilDef 19"/2" form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

### Flexible mounting

The 19"/2" standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

### Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

### Customizable

Are you looking for additional features and functions? MilDef specializes in customized solutions, to include change of connectors, chassis modifications, mounting solutions, etc. Contact your nearest MilDef Sales Office and we will help you tailor a solution to meet your exact requirements.

### Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

### Features

- 12-36 VDC
- Passively cooled

## Connector Interfaces

LAN (front)	• 1x ETH 1000BASE-T
5V DC (front)	• 1x USB 2.0
DC IN (back)	• 1x Power
Fiber (front)	• 1x ETH 100BASE-FX OM1

## Other Interfaces

1x Status indicator (front)

## Technical Specification

Blanking	Enable/disable all externally visible indicators from emitting light via the "blanking command"
LAN 1000BASE-T	1000BASE-T standard
LAN 100BASE-FX	100BASE FX standard with MM 1300 nm OM1 fiber
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Polarity protection	Protected against polarization failure on the power input in the voltage range of normal operation
Power consumption	5 W
Power input	12-36 VDC
Chassis material	Aluminum
Coating and color	Dupont AE0305-6603120 (RAL6031)
Cooling	Passively cooled
Dimensions	73 x 44 x 147 mm (2.9 x 1.8 x 5.8 in) (WxHxD)
Earth point	M6 12 mm
Surface treatment chassis	Chromit-Al
Weight	1 kg (2.2 lbs)
MTBF	Greater than 25,000 h
CE	Compliant

## Environmental Specification

Functional shock - Operating	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40 g 11 ms
High temperature - Operating	MIL-STD-810G, Method 501.5, Procedure II - Operation 55 °C (131 °F)
High temperature - Storage	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)

Humidity	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 % RH Ten 24 h cycles
----------	---

IP Class (Solid Particle Protection) IP Class 6X

IP Class (Water) IP Class X5

**Low air pressure - Rapid decompression** MIL-STD-810G, Method 500.5, Procedure III - Rapid decompression 75.2 kPa, corresponding to 2,438 m (8,000 ft) 17 kPa, corresponding to 12,192 m (40,000 ft)

**Low air pressure - Operating** MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4,572 m (15,000 ft)

**Low temperature - Operating** MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)

**Low temperature - Storage** MIL-STD-810G, method 502.5, Procedure I - Storage -40 °C (-40 °F)

**Noise level** Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance

**Salt fog** MIL-STD-810G Method: 509.5 5 % ± 1 % (by weight) Two cycles, 24 h wet + 24 h dry / cycle

**Temperature shock - Operating** MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) -40 °C (-40 °F)

**Vibration - Helicopter** MIL-STD-810G, Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter

**Vibration - Loose cargo** MIL-STD-810G, Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo

**Vibration - Tracked vehicles** MIL-STD-810G, Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles

**Vibration - Wheeled vehicles** MIL-STD-810G, Method: 514.6 , Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles

## EMC Specification

**EMI conducted CE102** MIL-STD-461F, Method CE102 BASIC CURVE 10 kHz to 10 MHz

## 19"/6 MC720

<b>EMI radiated RE102</b>	MIL-STD-461F Navy Mobile & Army 2 MHz - 18 GHz
<b>EMS conducted CS101</b>	MIL-STD-461F, Method CS101, conducted susceptibility, power leads. CURVE #1 30 Hz to 150 kHz
<b>EMS conducted CS114</b>	MIL-STD-461F Army, Ground 10 kHz - 200 MHz
<b>EMS conducted CS115</b>	MIL-STD-461F Conducted susceptibility, bulk cable injection, impulse excitation
<b>EMS conducted CS116</b>	MIL-STD-461F 10 kHz - 100 MHz
<b>EMS radiated RS103</b>	MIL-STD-461F Army 2 MHz - 1 GHz