

Model Comparison PWR2100 Series



	PWR2121	PWR2122	PWR2123	PWR2124	PWR2125	PWR2126
Product Picture						
Description	PDU with UPS	PDU with UPS	PDU with UPS	PDU with UPS	PDU with UPS	PDU with AC/DC and UPS
Power input	1x 110-230V AC EU plug	1x 110-230V AC US plug	1x 110-230V AC UK plug	1x DC (20-32V DC)	1x 18-32V DC	1x 105-125V AC
Power output	4x DC out	4x DC out	4x DC out	4x DC out	3x DC out	4x DC out
Capacity	192W / 250W peak (Battery Mode)	192W / 250W peak (Battery Mode)	192W / 250W peak (Battery Mode)	192W / 250W peak (Battery Mode)	192W / 250W peak (Battery Mode) 280 W / 364W Peak (DC mode)	192W / 250W peak (Battery Mode) TBD W / TBD W Peak (AC mode)
Battery type	Lithium-Ion	Lithium-Ion	Lithium-Ion	Lithium-Ion	Lithium-Ion	Lithium-Ion
Battery capacity	4 Ah	4 Ah	4 Ah	4 Ah	4 Ah	4 Ah
Management port	1x 100BASE-TX (Eth) 1x MilDef Service (RS232)	1x 100BASE-TX (Eth) 1x MilDef Service (RS232)	1x 100BASE-TX (Eth) 1x MilDef Service (RS232)	1x 100BASE-TX (Eth) 1x MilDef Service (RS232)	1x 100BASE-TX (Eth) 1x Console (RS485) 1x MilDef Service (RS232)	1x 100BASE-TX (Eth) 1x Console (RS485) 1x MilDef Service (RS232)