

19"/2[®] CS373



Full Server in a 19"/2[®] form factor

The 19"/2 Server i7 MIL CS373 packs high-performance computing power into a frame up to 75% smaller than standard 19" ruggger servers. This significantly reduces the i7's weight, energy consumption and heat production.

Small form factor

The MilDef 19"/2[®] form factor is optimized for reduced size, weight, and power (SWaP) to meet industry and military requirements without sacrificing reliability, ruggedness or performance.

Flexible mounting

The 19"/2[®] standard enables flexible mounting options for a wide array of integration scenarios. The unit can be mounted in a standard 19" rack, half racks, or directly on to a surface and at any angle.

Military-relevant rugged design

MilDef products are designed to operate in extreme environmental conditions and challenging electromagnetic operational scenarios. Operationally proven, MilDef products are actively employed in military operations in over 60 countries.

Customizable

Are you looking for additional features and functions? MilDef specializes in customized solutions, to include change of connectors, chassis modifications, mounting solutions, etc. Contact your nearest MilDef Sales Office and we will help you tailor a solution to meet your exact requirements.

Guaranteed performance

MilDef products are designed for the long lifecycles of military programs and come with a lifetime support program to ensure your equipment maintains peak performance for many missions to come.

We also guarantee the availability of spare parts for an additional 5 years after product end-of-life.

Features

- 12-32 VDC
- Passively cooled

Connector Interfaces

DC IN (front)	<ul style="list-style-type: none"> 1x Power
SERVICE (back)	<ul style="list-style-type: none"> 1x RS232 Service
X1 (front)	<ul style="list-style-type: none"> 1x VGA 1x AUDIO_IN 1x AUDIO_OUT 2x USB 1x RS232
X2 (front)	<ul style="list-style-type: none"> 4x 1000BASE-T 1x USB
X3 (front)	<ul style="list-style-type: none"> 1x DVI 3x USB 1x Remote Power On 2x RS232

Other Interfaces

3x MilDef Disk Slot (front)
1x RAID indicator (front)
1x System button (front)

Technical Specification

Blanking	Double-pressing the System button
LAN 1000BASE-T	1000BASE-T standard
LAN POE compatibility	Type 1 (PoE) and 802.3at Type 2 (PoE+)
MIL-STD-1275D	5.3.2.2 5.3.2.3 5.3.2.4
Polarity protection	Protected against polarization failure on the power input in the voltage range of normal operation
Power consumption	Max 105 W Idle 20 W Standby 6 W
Power input	12-32 VDC
Chassis material	Aluminum
Coating and color	Dupont AE0305-6603120 (RAL6031)
Cooling	Passively cooled
Dimensions	220 x 87.9 x 332 mm (8.7 x 3.5 x 13.1) (WxHxD)
Earth point	M6 12 mm
Rack mounting depth	400 mm (17.4 in)
Surface treatment chassis	Chromit-Al
Weight	8 kg (17.7 lbs)
MTBF	Greater than 25,000 h
CE	Compliant

Environmental Specification

Functional shock - Operating	MIL-STD-810G, Method 516.6, Procedure I - Functional Shock. Table 516.6-II, Terminal peak sawtooth pulse, Ground equipment 40 g 11 ms
High temperature - Operating	MIL-STD-810G, Method 501.5, Procedure II - Operation 55 °C (131 °F)
High temperature - Storage	MIL-STD-810G, Method 501.5, Procedure I - Storage 71 °C (160 °F)
Humidity	MIL-STD-810G, Method 507.5, Procedure II - Aggravated 95 ± 4 % RH Ten 24 h cycles
IP Class (Water)	IP Class X4
IP Class (solid foreign object)	IP Class 5X
Low air pressure - Rapid decompression	MIL-STD-810G, Method 500.5, Procedure III - Rapid decompression 75.2 kPa, corresponding to 2,438 m (8,000 ft) 17 kPa, corresponding to 12,192 m (40,000 ft)
Low air pressure - Operating	MIL-STD-810G, method 500.5, Procedure II - Operation/Air Carriage 4,572 m (15,000 ft)
Low temperature - Operating	MIL-STD-810G, method 502.5, Procedure II - Operation -40 °C (-40 °F)
Low temperature - Storage	MIL-STD-810G, method 502.5, Procedure I - Storage -40 °C (-40 °F)
Noise level	Maximum noise level of 40 dB SPL A-weighting at 1 m (3.3 ft) distance
Salt fog	MIL-STD-810G Method: 509.5 5 % ± 1 % (by weight) Two cycles, 24 h wet + 24 h dry / cycle
Temperature shock - Operating	MIL-STD 810G, method 503.5 procedures I - C, - Multi-cycle shocks from constant extreme temperature 55 °C (131 °F) -40 °C (-40 °F)
Vibration - Helicopter	MIL-STD-810G, Method 514.6, Procedure I - General vibration, Category 14 - Rotary wing aircraft - helicopter

Vibration - Loose Cargo MIL-STD-810G, Method 514.6, Procedure II - Loose cargo transportation, Category 5 - Truck/trailer - loose cargo

Vibration - Tracked Vehicles MIL-STD-810G, Method: 514.6, Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, tracked vehicles

Vibration - Wheeled Vehicle MIL-STD-810G, Method: 514.6, Procedure 1 - General Vibration, Category 20 - Ground vehicles - ground mobile, wheeled vehicles

EMC Specification

EMI conducted CE102 MIL-STD-461F, Method CE102
BASIC CURVE
10 kHz to 10 MHz

EMI radiated RE102 MIL-STD-461F
Navy Mobile & Army
2 MHz - 18 GHz

EMS conducted CS101 MIL-STD-461F, Method CS101, conducted susceptibility, power leads.
CURVE #1
30 Hz to 150 kHz

EMS conducted CS114 MIL-STD-461F
Army, Ground
10 kHz - 200 MHz

EMS conducted CS115 MIL-STD-461F
Conducted susceptibility, bulk cable injection, impulse excitation

EMS conducted CS116 MIL-STD-461F
10 kHz - 100 MHz

EMS radiated RS103 MIL-STD-461F
Army
2 MHz - 1 GHz