






Model Comparison ESW1100 Series



	ESW1101	ESW1121	ESW1122	ESW1123	ESW1124	ESW1127
Product Picture						
Description	MIL	Industrial	Industrial	Industrial	Industrial	Industrial
Management	Not supported	Not supported	Not supported	Not supported	Not supported	Not supported
VLAN	Not supported	Not supported	Not supported	Not supported	Not supported	Not supported
Ethernet (copper)	8 x 1000Base-T (38999)	8 x 1000Base-T (RJ45)	8 x 1000Base-T (RJ45)	8 x 1000Base-T (RJ45)	8 x 1000Base-T (RJ45)	8 x 1000Base-T (RJ45)
Ethernet (fiber)	-	-	-	2x 1000Base-SX (LC)	2x 1000Base-SX (LC)	2x 1000Base-LX (LC)
PoE Power	-	-	110W (18-32V DC) 41W (12-18V DC)	-	110W (18-32V DC) 41W (12-18V DC)	-
Power Consumption	< 10 W max	< 10 W max	< 15 W max (w/o. PoE) < 145W max (w. full PoE)	< 15 W max	< 15 W max (w/o. PoE) < 150W max (w. full PoE)	< 15 W max
Temperature (operating)	-40°C to 65°C*	-40°C to 65°C*	-40°C to 65°C (w/o. PoE) -40°C to 55°C (w. full PoE)	-40°C to 65°C*	-40°C to 65°C (w/o. PoE) -40°C to 55°C (w. full PoE)	-40°C to 65°C*
Power	10-32 VDC	10-32 VDC	12-32 VDC	10-32 VDC	12-32 VDC	10-32 VDC
Power connector	ITT/CA Bayonet	ITT/CA Bayonet	ITT/CA Bayonet	ITT/CA Bayonet	ITT/CA Bayonet	ITT/CA Bayonet

* 71°C option available