



Model Comparison - Tablets



	RM200 Series	RM2100 Series
Appearance		
Platform	Cisco ESR5915	Cisco ESR6300 (+ Cisco ESS3300 as an option)
Software	IOS	IOS-XE
Ethernet Interfaces	2x 100 Mbps WAN 3x 100 Mbps LAN	2x 1 Gbps WAN 4x 1 Gbps LAN (Additional 10x Eth with ESS3300)
Console	1x Serial Console 1x USB Console (not all variants)	1x Serial Console 1x USB Console (not all variants)
USB	2x USB (power only)	USB 3
Power over Ethernet	No	Yes (Up to 105W)
Serial Port	No	Yes (1 port)
Crypto Throughput	15 Mbps	Up to 350 Mbps depending on license. (Default 50 Mbps)
MGMT tools	No	Yes (Cisco DNA, SD-WAN*, WEBUI, IOx)
CME support	Yes	Yes
Case	Aluminum	Aluminum
Standards	IP54, MIL-STD-810F, MIL-STD-461F, MIL-STD-1275D	IP65, MIL-STD-810G, MIL-STD-461F, MIL-STD-1275D
Temperature	Operational: -40°C to +71°C Storage: -40°C to +71°C	RM2121 (w/o ESS3300 card): Operational: TBD Storage: -40°C to +71°C
Dimensions (WxDxH)	220 x 202 x 44 mm (RM201)	RM2121 (w/o ESS3300 card): 220 x 225 x 44 mm (8.7 x 8.9 x 1.7 inch) RM2139 (w. ESS3300): 220 x 354 x 44 mm (8.7 x 13.9 x 1.7 inch)
Weight	2,5 kg (RM201)	RM2121 (w/o ESS3300 card): TBD RM2139 (w. ESS3300): 3.8 kg (8.4 lbs)