

## Model Comparison KSW4100



	KSW4101	KSW4102	KSW4103
<b>Product Picture</b>			
<b>Connector type</b>	Circular MIL	Circular MIL	Circular MIL
<b>Function</b>	Extender for DVI and USB over a fiber link	Extender for DVI and USB over a fiber link	Dual extenders for DVI and USB over a fiber link
<b>Extender config</b>	Remote side	Local side	Remote side
<b>Interfaces</b>	1x Fiber link to Local (Video, AVR, USB) 1x DVI 2x USB2.0 1x MilDef Service 1x DC in	1x Fiber link to Local (Video, AVR, USB) 1x DVI 1x USB2.0 1x Remote KVM 1x MilDef Service 1x DC in	2x Fiber link to Local (Video, AVR, USB) 2x DVI 3x USB2.0 2x MilDef Service 1x DC in 1x Swtich for channel selection
<b>Power connector</b>	ITT CA (ITS)	ITT CA (ITS)	ITT CA (ITS)
<b>Graphics resolution</b>	1920 x 1200 @ 60Hz	1920 x 1200 @ 60Hz	1920 x 1200 @ 60Hz
<b>Power consumption (max)</b>	15W	10W	20W
<b>Power input</b>	12-32V DC	12-32V DC	12-32V DC
<b>Dimensions w/o front connectors (WxDxH)</b>	170 x 120.2 x 49.5 mm (6.7 x 4.7 x 1.9 inch)	110 x 194 x 43.4 mm (4.3 x 7.6 x 1.7 inch)	170 x 128 x 90 mm (6.7 x 5 x 3.5 inch)
<b>Weigth</b>	1.1 kg (2.4 lbs)	1 kg (2.2 lbs)	1.8 kg (4 lbs)
<b>MTBF</b>	170 353 h	192 482 h	TBD